

(19)

Europäisches Patentamt
European Patent Office
Office européen des brevets



(11)

EP 1 428 924 A1

(12)

EUROPEAN PATENT APPLICATION

(43) Date of publication:
16.06.2004 Bulletin 2004/25

(51) Int Cl.7: D06F 37/30

(21) Application number: 03257739.7

(22) Date of filing: 09.12.2003

(84) Designated Contracting States:
AT BE BG CH CY CZ DE DK EE ES FI FR GB GR
HU IE IT LI LU MC NL PT RO SE SI SK TR
Designated Extension States:
AL LT LV MK

(30) Priority: 10.12.2002 KR 2002078337
02.12.2003 KR 2003086841

(71) Applicant: LG Electronics Inc.
Seoul 150-721 (KR)

(72) Inventors:
• Kim, Gon
Gyeongsangnam-do (KR)
• Hur, Chi Wan
Changwon-si, Gyeongsangnam-do (KR)

• Kang, Yu Beom
Changwon-si, Gyeongsangnam-do (KR)
• Je, Sang Man
Koje-si, Gyeongsangnam-do (KR)
• Choi, Kang Mo
Masan-si, Gyeongsangnam-do (KR)
• Kim, Jae Kyum
Gimhae-si, Gyeongsangnam-do (KR)
• Kwon, Ho Cheol
Changwon-si, Gyeongsangnam-do (KR)


(74) Representative: Neobard, William John et al
Kilburn & Strode
20 Red Lion Street
London WC1R 4PJ (GB)

(54) Drum type washing machine

(57) Drum type washing machine including a tub of plastic having a wall for holding washing water therein and mounting a driving part thereon, a drum rotatably arranged inside of the tub, a shaft passed through the tub and connected to the drum for transmission of a driving power from a motor to the drum, at least one bearing for supporting the shaft, a bearing housing having a bearing supporting part formed as a sleeve, and a stator fastening part extended in a radial direction from the bearing supporting part, wherein both of the bearing supporting part and the stator fastening part are inserted in a tub rear wall, while stator fastening holes in the stator fastening part are exposed, a rotor engaged to a rear end part of the shaft to form the motor together with the stator, and the stator mounted on the stator fastening part of the bearing housing with fastening members on an inner side of the rotor to form the motor together with the rotor, wherein the stator includes an annular helical type core having multiple layers formed by winding a steel plate having tooth portions and a base part in a helix starting from a bottom layer to a top layer, an insulator having the helical type core encapsulated therein, a coil wound on the tooth portions, and fastening parts formed as a unit with the insulator, having fastening holes projected toward an inside of the helical type core for fastening the stator to the bearing housing, thereby reducing a weight of required material, simplifying an as-

sembly process, and assure stable mounting of the stator on the tub.

FIG. 5



EP 1 428 924 A1

Description

[0001] The present invention relates to drum type washing machines, and more particularly, to an improved structure of a driving part of a direct drive type drum type washing machine which employs an outer rotor type brushless DC motor.

[0002] In general, a drum type washing washes laundry by using a friction force between a drum rotated by a driving power of a motor and the laundry in a detergent with washing water. The laundry is introduced into the drum, and is washed with little damage, and little entangling. The action has pounding, and rubbing washing effects.

[0003] In a prior drum type washing machines, there are an indirect drive type in which the driving power of the motor is transmitted to the drum through a belt wound on a motor pulley and a drum pulley indirectly, and a direct drive type in which the brushless DC motor is connected to the drum directly, to transmit the driving power of the motor to the drum, directly.

[0004] Machines in which the driving power of the motor is transmitted to the drum, not directly, but indirectly using a motor pulley and a drum pulley, lose energy loss and create noise in the course of power transmission.

[0005] Hence, there is a trend increasingly to use direct drive type drum type washing machines with brushless d.c. motors, as these address the problems of the indirect drive type drum type washing machines. A prior direct drive type drum type washing machine will be described with reference to FIG. 1, briefly. FIG. 1 illustrates a longitudinal section of a related art drum type washing machine. Referring to FIG. 1, a prior drum type washing machine is provided with a tub 2 mounted inside of a cabinet 1, and a drum 3 rotatably mounted centrally inside the tub 2. There is a motor in rear of the tub 2, wherein a stator 6 is fixed to a rear wall of the tub, and a rotor 5 surrounds the stator 6, and is connected to the drum 3 with a shaft passed through the tub.

[0006] There is also a metallic tub supporter between a tub rear wall and the stator having a shape almost the same with an outer shape of the tub rear wall. The supporter is fixed to the tub rear wall in fastening the stator for supporting a load of the stator, and maintaining concentricity of the stator.

[0007] A door 21 is mounted on a front part of the cabinet 1, and a gasket 22 is disposed between the door 21 and the tub 2.

[0008] A hanging spring 23 is disposed between an inside surface of an upper part of the cabinet 1, and an upper part of an outside circumferential surface of the tub 2, and a friction damper 24 is disposed between the inside surface of a lower part of the cabinet 1, and a lower part of the outside circumferential surface of the tub 2.

[0009] FIG. 2 illustrates a perspective outside view of the stator in FIG. 1, and FIG. 3 illustrates a perspective view of a sectional type core SC applied to the stator in

FIG. 2.

[0010] In prior method for fabricating the stator core, a sheet of metal plate is pressed to form a core unit having tooth portions 151, a base part 150, and a round part 500 opposite to the tooth portions 151 for forming fastening hole 500a therein. The core units are stacked to form a core unit assembly, and the core unit assemblies are connected to each other in a circumferential direction, to complete fabrication of the stator core, called the sectional type core SC.

[0011] The round part provides the fastening hole 500a for fixing the stator 6 to the rear wall of the tub, and enduring a fastening force of a bolt.

[0012] However, the method for fabricating the stator 6 by means of the sectional type cores SC has, not only a complicated fabrication process, but also much wastage of material.

[0013] Therefore, even if a helical type core HC is favourable, in which a sheet of steel plate having the tooth portions 151 and the base part 150 is stacked turning in a helix, since it is required to bend the sheet of metal punched out in a form of a band into the helix, the helical type core has a drawback in that the round part for fixing the stator to the tub can not be formed on an inner side of the core.

[0014] This is because, if the round part 500 is formed on the inner side of the core in fabrication of the helical core HC, a large width of the core at a part having the round part formed thereon impedes bending of the core. Therefore, currently, a stator structure is required, in which a function the same with the round part of the sectional type core SC is made to be carried out, not by the core itself, but by other part, for employing the helical type core HC.

[0015] For reference, a reason why it is important to secure an adequate rigidity of the round part having the fastening hole formed in for fixing the stator to the tub is as follows.

[0016] The washing machine that rotates the drum directly by using the brushless d.c. motor has the stator mounted on a rear part of the tub, directly. In a case of the motor for a large capacity drum type washing machine with more than 1.5kg of stator net weight, and a spinning speed in a range of 600 - 2000 RPM, it is liable that a bolt fastened part of the stator 6 is broken due to the stator weight, vibration in the high speed rotation, and shaking and deformation of the rotor 5.

[0017] Particularly, in a case of the drum type washing machine, in which the brushless d.c. motor is used, and the stator 6 is fixed to the tub rear wall, where an axis direction of the stator 6 is substantially parallel to ground, the vibration generated in operation of the washing machine causes intensive damage to the fastening part of the stator 6 to the tub rear wall.

[0018] Thus, adequate rigidity of the round part having the fastening hole formed therein is very important in fixing the stator 6 to the tub.

[0019] There is a trend to increase the capacity of

washing machines as the time goes by. Problems may arise in this, for example the tub to which the stator is fastened may be damaged if the stator has a weight more than 1.5kg when the axis of the stator is parallel to the ground.

[0020] Therefore, in order to prevent occurrence of the damage, in the prior structure, in general a metal tub supporter is lined, when a process for fastening the tub supporter to the tub rear wall is required in addition to an assembly line. This reduces productivity.

[0021] Accordingly, embodiments of the present invention may substantially obviate one or more of the problems due to limitations and disadvantages of the related art.

[0022] An object of embodiments of the present invention is to provide a drum type washing machine, which has an outer rotor type motor with a stator of which material and weight required for fabrication can be reduced, fabrication of which can be simplified, and secure mounting of which on the tub is possible.

[0023] Another object of embodiments of the present invention is to provide a drum type washing machine, in which a tub can sustain weight and vibration of a brushless d.c. motor for a washing machine mounted on a tub wall directly, which motor has a net stator weight more than 1.5kg, and variable rotational speed of 0 - 2000 RPM or over.

[0024] Yet another object of embodiments of the present invention is to provide a drum type washing machine, which can dispense with a tub supporter fastening process from an assembly line, that can secure a supporting force of the tub rear wall to the stator, and simplifies an assembly process.

[0025] A further object of embodiments of the present invention is to provide a drum type washing machine, which enables a service man to carry out maintenance in repair and replacement of components.

[0026] According to one aspect of the invention there is provided a drum type washing machine having a tub of plastic having a wall for holding washing water therein and mounting a driving part thereon, a drum rotatably arranged inside of the tub, a shaft passed through the tub and connected to the drum for transmission of a driving power from a motor to the drum, at least one bearing for supporting the shaft, a bearing housing having a sleeve form of bearing supporting part, and a stator fastening part extended in a radial direction from the bearing supporting part, wherein both of the bearing supporting part and the stator fastening part are inserted in a tub rear wall, while stator fastening holes in the stator fastening part are exposed, a rotor engaged to a rear end part of the shaft to form the motor together with the stator, and the stator mounted on the stator fastening part of the bearing housing with fastening members on an inner side of the rotor to form the motor together with the rotor, wherein the stator includes an annular helical type core having multiple layers formed by winding a steel plate having tooth portions and a base part in a

helix starting from a bottom layer to a top layer, an insulator having the helical type core encapsulated therein, a coil wound on the tooth portions, and fastening parts formed as a unit with the insulator, having fastening holes projected toward an inside of the helical type core for fastening the stator to the bearing housing.

In other aspect of the present invention, there is provided a drum type washing machine including a tub of plastic having a wall for holding washing water therein and mounting a driving part thereon, a drum rotatably arranged inside of the tub, a shaft passed through the tub and connected to the drum for transmission of a driving power from a motor to the drum, at least one bearing for supporting the shaft, a bearing housing having a sleeve form of bearing supporting part, and a stator fastening part extended in a radial direction from the bearing supporting part, wherein both of the bearing supporting part and the stator fastening part are inserted in a tub rear wall, while stator fastening holes in the stator fastening part are exposed, a rotor engaged to a rear end part of the shaft to form the motor together with the stator, and the stator mounted on the stator fastening part of the bearing housing with fastening members on an inner side of the rotor to form the motor together with the rotor, wherein the stator includes an annular helical type core having multiple layers formed by winding a steel plate having tooth portions and a base part in a helix starting from a bottom layer to a top layer, an insulator having the helical type core encapsulated therein, a coil wound on the tooth portions, and fastening parts formed as a unit with the insulator, having three or more than three fastening holes projected toward an inside of the helical type core for fastening the stator to the bearing housing.

[0027] In another aspect of the present invention, there is provided a drum type washing machine including a tub of a plastic having a wall for holding washing water therein and mounting a driving part thereon a drum rotatably arranged inside of the tub, a shaft passed through the tub and connected to the drum for transmission of a driving power from a motor to the drum, at least one bearing for supporting the shaft, a bearing housing having a sleeve form of bearing supporting part inserted in the tub rear wall, and a stator fastening part formed as a unit with the bearing supporting part extended from the bearing supporting part exposed to an outside of the tub, with stator fastening holes formed in an exposed part of the stator fastening part, a rotor engaged to a rear end part of the shaft to form the motor together with the stator, and the stator mounted on the stator fastening part of the bearing housing with fastening members on an inner side of the rotor to form the motor together with the rotor, wherein the stator includes an annular helical type core having multiple layers formed by winding a steel plate having tooth portions and a base part in a helix starting from a bottom layer to a top layer, an insulator having the helical type core encapsulated therein, a coil wound on the tooth portions, and fastening parts formed as a unit with the insulator, having fastening

holes projected toward an inside of the helical type core for fastening the stator to the bearing housing.

In further object of the present invention, there is provided a drum type washing machine including a tub of a plastic having a wall for holding washing water therein and mounting a driving part thereon, a drum rotatably arranged inside of the tub, a shaft passed through the tub and connected to the drum for transmission of a driving power from a motor to the drum, at least one bearing for supporting the shaft, a bearing housing having a sleeve form of bearing supporting part inserted in the tub rear wall, and a stator fastening part formed as a unit with the bearing supporting part extended in a radial direction from the bearing supporting part exposed to an outside of the tub, with stator fastening holes formed in an exposed part of the stator fastening part, a rotor engaged to a rear end part of the shaft to form the motor together with the stator, and the stator mounted on the stator fastening part of the bearing housing with fastening members on an inner side of the rotor to form the motor together with the rotor, wherein the stator includes an annular helical type core having multiple layers formed by winding a steel plate having tooth portions and a base part in a helix starting from a bottom layer to a top layer, an insulator having the helical type core encapsulated therein, a coil wound on the tooth portions, and fastening parts formed as a unit with the insulator, having three or more than three fastening holes projected toward an inside of the helical type core for fastening the stator to the bearing housing.

In still further object of the present invention, there is provided a drum type washing machine including a tub of plastic having a wall for holding washing water therein and mounting a driving part thereon, a drum rotatably arranged inside of the tub, a shaft passed through the tub and connected to the drum for transmission of a driving power from a motor to the drum, at least one bearing for supporting the shaft, a bearing housing having a sleeve form of bearing supporting part, and a stator fastening part extended in a radial direction from the bearing supporting part, wherein both of the bearing supporting part and the stator fastening part are inserted in a tub rear wall, while stator fastening holes in the stator fastening part are exposed, a rotor engaged to a rear end part of the shaft to form the motor together with the stator, and the stator mounted on the stator fastening part of the bearing housing with fastening members on an inner side of the rotor to form the motor together with the rotor.

In yet further aspect of the present invention, there is provided a drum type washing machine including a tub of plastic having a wall for holding washing water therein and mounting a driving part thereon, a drum rotatably arranged inside of the tub, a shaft passed through the tub and connected to the drum for transmission of a driving power from a motor to the drum, at least one bearing for supporting the shaft, a bearing housing having a sleeve form of bearing supporting part inserted in the

tub rear wall, and a stator fastening part formed as a unit with the bearing supporting part extended in a radial direction from the bearing supporting part exposed to an outside of the tub, with stator fastening holes formed in an exposed part, a rotor engaged to a rear end part of the shaft to form the motor together with the stator; and the stator with a weight heavier than 1.5kg mounted on the stator fastening part of the bearing housing with fastening members on an inner side of the rotor to form the motor together with the rotor.

[0028] In still yet further aspect of the present invention, there is provided a drum type washing machine including a tub having a wall for holding washing water therein and mounting a driving part thereon, and a sleeve form of bearing supporting part for supporting bearings, in which both the tub and the bearing supporting part are formed as one unit, a drum rotatably arranged inside of the tub, a shaft passed through the tub and connected to the drum for transmission of a driving power from a motor to the drum, at least one bearing inside of the bearing supporting part for supporting the shaft, a rotor engaged to a rear end part of the shaft to form the motor together with the stator, and the stator mounted on the tub on an inner side of the rotor and an outer side of the bearing supporting part with fastening members, wherein the stator includes an annular helical type core having multiple layers formed by winding a steel plate having tooth portions and base part in a helix starting from a bottom layer to a top layer, an insulator having the helical type core encapsulated therein, a coil wound on the tooth portions, and fastening parts formed as a unit with the insulator, having fastening holes projected toward an inside of the helical type core for fastening the stator to the bearing housing.

It is to be understood that both the foregoing description and the following detailed description of the present invention are exemplary and explanatory and are intended to provide further explanation of the invention claimed.

[0029] Exemplary embodiments of the invention will now be described by reference to the accompanying drawings, in which:

FIG. 1 illustrates a schematic view through a longitudinal section of a prior direct drive, drum type washing machine;

FIG. 2 illustrates a perspective view of a prior stator;

FIG. 3 illustrates a perspective view of a sectional type core;

FIG. 4 illustrates a schematic longitudinal section of a direct drive, drum type washing machine embodying the present invention;

FIG. 5 illustrates an enlarged longitudinal sectional view of part 'A' in FIG. 4;

FIG. 6 illustrates a cut away perspective view of a tub rear wall;

FIG. 7 illustrates a perspective view of the unitary bracket and bearing housing in FIG. 5;

FIG. 8 illustrates a backside perspective view of FIG. 7;

FIG. 9 illustrates a section across a line I-I in FIG. 7;

FIG. 10 illustrates a perspective view of the stator in FIG. 5;

FIG. 11 illustrates a perspective view of the helical type core in FIG. 10;

FIG. 12A illustrates a plan view of key parts of the stator in FIG. 10, and FIG. 12B illustrates a perspective view of key parts of the stator in FIG. 10;

FIG. 13 illustrates a perspective view of a stator in a driving part of a drum type washing machine embodying the present invention; and

FIG. 14 illustrates a longitudinal section of a drum type washing machine embodying the present invention.

[0030] A drum type washing machine has a tub 2 for holding washing water inside of a cabinet 1, with a wall for fixing a driving part thereto, a drum 3 inside of the tub 2, a shaft 4 connected to the drum 3 with a shaft for transmission of a driving power from a motor to the drum 3, and a bearing for supporting the shaft 4. In this embodiment the tub 2 is formed of a plastic, and includes a metal bearing housing 7 at a central part of a rear wall of the tub 2 both for supporting the bearings at both ends of an outside circumferential surface of the shaft 4 and fastening the stator 6.

[0031] The bearing housing 7 is formed of an aluminum alloy and the like, and integrated with the tub rear wall by inserting the bearing housing 7 in a mold in an injection molding of the tub 2 of plastic.

[0032] Referring to FIG. 5, the bearing housing 7 includes a bearing supporting part 7a of a sleeve form for supporting the bearings, a stator fastening part 7b formed as a unit with the bearing supporting part 7a extended from a rear end of the bearing supporting part 7a in a radial direction, and stator fastening holes 700b in the stator fastening part 7b, wherein both the bearing supporting part 7a and the stator fastening part 7b are inserted in the tub 2 rear wall, when only the stator fastening holes 700b are exposed.

[0033] Referring to FIGS. 7 and 8, the stator fastening part 7b, extended from the sleeve form of bearing supporting part 7a in the radial direction outwardly, includes stepped areas 70b-1 each having at least one step in the outward extension in a direction of the outward extension, and flat areas 70b-2 each between adjacent stepped areas 70b-1, wherein the stepped areas 70b-1 and the flat areas 70b-2 are connected to each other, respectively.

[0034] That is, the stator fastening part 7b includes the stepped areas 70b-1 each having steps as the stepped area 70b-1 extends in an outward radial direction, and flat areas 70b-2 between the stepped areas 70b-1, wherein each of the areas 70b-1 extended from an upper end of the bearing supporting part 7a in the outward radial direction is bent down at preset intervals

as the stepped area 70b-1 extends in the outward radial direction, and each of the areas 70b-2 connected to a lower end of the bearing housing 7 is flat.

[0035] There is a resin stuffing groove 750a around the upper part of the bearing housing 7 for enhancing a bonding force with the tub 2 in the insert injection molding.

[0036] Referring to FIGS. 6 and 7, there is a positioning hole 710b formed adjacent to a stator fastening hole 700b of the stator fastening part 7b in correspondence to a positioning projection on the stator 6.

[0037] Referring to FIG. 6, there is a boss 200 at a part of the tub rear wall opposite to each of the stator fastening holes 700b for preventing the stator fastening part 7b from coming into direct contact with the stator 6, thereby preventing an insulator of the stator 6 from being broken due to a fastening force applied thereto in mounting the stator 6.

[0038] It is also preferable that the stator fastening part 7b has a circumferential rib 720b at a position spaced a distance from an axis of the bearing supporting part 7a for increasing a bonding force with the plastic in the injection molding of the tub 2. Though it is preferable that there are fastening bosses 70b each with a stator fastening hole 700b on the rib 720, it is not necessarily required to form the fastening holes 700b on the rib 720b.

[0039] In addition to this, there are circumferential and radial reinforcing ribs 201 on a region excluding the bearing housing stepped area of the tub rear wall for reinforcing the tub rear wall.

[0040] In the meantime, different from the foregoing stator fastening part 7b, the stator fastening part 7b may be an extension from the sleeve form of the bearing supporting part 7a the same with the foregoing stator fastening part 7b, but separated at regular intervals in a circumferential direction to form a plurality of separated radial segments.

[0041] Referring to FIGS. 5 and 6, the bearing housing 7 of metal has a step 8a in an inside circumferential surface for supporting, and preventing the bearings 600a on the inside circumferential surface from breaking away from the bearing housing 7.

[0042] A front part of the shaft 4 is fixed to a spider 10 in a rear wall of the drum 3, and a section of the shaft 4 from an exposed part in rear of the spider 10 to a front bearing 600a has a brass bushing 11 press fit thereon for preventing the shaft 4 from rusting, with a sealing member 12 fitted on an outside surface of the bushing 11 for preventing infiltration of water toward the bearing.

[0043] The shaft 4 has the rotor 5 of the direct drive motor mounted at a centre of rear end thereof, on an inner side of which the stator 14 is positioned, that is mounted on the tub rear wall to form the direct drive motor together with the rotor 5.

[0044] Referring to FIG. 5, the rotor 5, formed of steel plate, has a circumferential bent part with a seating surface 130 for seating magnets M placed on an inside sur-

face of a side wall 13b extended forward from an edge of a rear wall of the rotor 5, and a hub 132 in a centre part of the rear wall 13a having through holes for passing fastening members 15a, such as bolts, in mounting the rotor 5 on the shaft 4.

[0045] It is preferable that the rotor 5 is formed by pressing.

[0046] The rotor 5 has a plurality of radial cooling fins 133 around the hub 132 for blowing air toward the stator 6 when the rotor 5 rotates, to cool down heat from the stator 6. Each of the cooling fins 133 has a length in the radial direction.

[0047] The cooling fin 133 is formed by lancing to be bent at 90° from the rear wall to direct an opened side of the rotor 5, and a through hole 134 formed in the lancing serves as an air hole.

[0048] The rotor 5 has embossing 135 between adjacent cooling fins 133 of the rear wall 13a for reinforcing the rotor 5, and drain holes 136 in the embossing 135.

[0049] The rotor 5 has fastening holes 137 for fastening a connector 16 engaged with a rear end part of the shaft 4 in rear of a rear bearing 600b by means of serration, and positioning holes 138 for positioning the connector in mounting the connector on the shaft 4, both of which fastening holes 137 and positioning holes 138 are formed around the through hole 131 in the hub 132 at regular intervals.

[0050] The connector 16 is formed of plastic having a vibration mode different from the rotor 5 of steel plate, and serves as a bushing for the rotor, too. The connector 16 has serration 164 fit to the serration 400 in the rear end part of the shaft 4.

[0051] The tub rear wall has a hub part for putting the bearing supporting part 7a of the bearing housing 7 therein in the injection molding of the tub 2.

[0052] According to this, an embodiment of the present invention permits to dispense with the tub supporter which is essential in the prior art, to reduce assembly man power in an assembly line, and improve productivity.

[0053] That is, embodiments of the present invention permit dispensing with the tub supporter, which is a separate part having an almost same outside shape with the tub rear wall, fixed to, and holds the tub rear wall in mounting the stator 6, and maintains a concentricity of the stator 6.

[0054] Referring to FIG. 10, the stator 6 includes a helical type core HC, an insulator 144 having the helical type core HC encapsulated therein, a coil wound around tooth portions 151 of the helical type core HC, and fastening parts 143 molded as a unit with the insulator 144 projected toward an inside of the helical type core HC from three, or more than three places, and in general weighs more than 1.5kg as the capacity of the drum type washing machine becomes larger.

[0055] The helical type core HC has multiple layers formed by winding a steel plate having the tooth portions and the base part in a helix starting from a bottom layer

to a top layer, with the tooth portions 151 projected outwardly in a radial direction from the base part. The base part 150 has recesses 152 for reducing stress in the winding of the helical type core.

5 [0056] The multiple layers of the helical type core HC are fastened with rivets 153 passed through through holes in the base part 150. A starting part and an end part of the helical type core HC may be welded at the base parts 150 in contact thereto. The recess 152 in the base part 150 may be rectangular, trapezoidal, or an arc.

10 [0057] Referring to FIGS. 12A and 12B, in the stator 6 having three or more than three fastening parts 143 formed as a unit with the insulator so as to be projected in a radial direction toward inside from the inside circumferential surface of the helical type core, each of the fastening parts 143 is formed to meet a condition of $a \geq b$, where "a" denotes a length of the tooth portion 151 from an outer edge of the base part 150, and "b" denotes a distance from an inner edge of the base part 150 to a centre of the fastening hole 143a.

20 [0058] The fastening part 143 has a height greater than 20% of a total core stack height, and preferably equal to the total core stack height.

[0059] The fastening part 143 has at least one cavity 25 143c for damping vibration at the time of motor driving, and a positioning pin 143b fit to the positioning hole 710b in the stator fastening part exposed in a state inserted in the tub rear wall.

30 [0060] A metal tube 143p or a spring pin is forcibly inserted in the fastening hole 143a of the fastening part 143.

[0061] The operation of the driving part of the drum type washing machine of the present invention will be described.

35 [0062] Under the control of a controller (not shown) attached to a panel for driving the motor, if current flows to the coils 142 in the stator 6 in succession, to rotate the rotor 5, the shaft 4 engaged with the connector 16 having the rotor 5 fixed thereto by means of serration rotates. Power is transmitted to the drum 3 through the shaft 4, to rotate the drum 3.

[0063] Performance of the foregoing drum type washing machine will be described.

40 [0064] Since the tub 2 is formed of a heat resistant plastic, the tub 2 is light, and since the tub 2 is injection molded, the tub 2 is easy to fabricate.

[0065] Since the bearing housing 7 is formed of a metal, such as an aluminium alloy, which shows little thermal deformation even at a high temperature, the bearing housing 7 can be used in the drum type washing machine having the spinning cycle.

45 [0066] Since the bearing housing 7 of metal is inserted in the hub of the tub rear wall at the time of injection molding of the tub 2 of plastic, to form an integrated type tub 2 and bearing housing 7, that permits to dispense with the additional process of mounting the bearing housing 7 on the tub rear wall, thereby simplifying the assembly process, and reduce an assembly man power.

[0067] Referring to FIG. 11, the recess 152 in the base part 150 of the stator 6 reduces a stress in winding the core, thereby permitting an easy and small power winding.

[0068] Especially, referring to FIG. 12A, in the stator 6 having three or more than three fastening parts 143 formed as a unit with the insulator so as to be projected in a radial direction toward inside from the inside circumferential surface of the helical type core, each of the fastening parts 143 is formed to meet a condition of $a \geq b$, where "a" denotes a length of the tooth portion 151 from an outer edge of the base part 150, and "b" denotes a distance from an inner edge of the base part 150 to a centre of the fastening hole 143a.

[0069] The condition is set taking a case into account, in which, even though the closer the position of the fastening hole 143a to a point a load exerts thereon, the better in view of reduction of a torque, the position of the fastening hole 143a set at a position close excessively to the point a load exerts thereon leads to a bolt of smaller diameter, to require an excessively many number of bolts. Referring to FIG. 12B, the fastening part 143 has a height greater than 20% of a total core stack height, otherwise the fastening part 143 is liable to break due to vibration caused by motor driving. Especially, the fastening part 143 may have a height equal to or higher than the total core stack height.

[0070] However, because an excessively high fastening part 143 increases a total width of the driving part, and reduces a washing capacity of the washing machine, the height of the fastening part 143 is limited not to exceed two times of the total core stack height.

[0071] The cavity 143c in the fastening part 143 dampens vibration at the time of motor driving, to improve mechanical reliability of the stator 6.

[0072] The positioning pin 143b on the fastening part 143 fits to the positioning hole 710b in the tub 2, thereby permitting an easy mounting of the stator 6 on the tub 2.

[0073] The sleeve form of bearing supporting part 7a for supporting bearings fitted therein, and the stator fastening part 7b for fastening the stator 6 thereto, of the bearing housing 7, both of which are formed as a unit, can dispense with the related art tub supporter.

[0074] The boss 200 at a part of the tub rear wall opposite to each of the stator fastening holes 700b prevents the stator fastening part 7b from coming into direct contact with the stator 6, thereby preventing the insulator of the stator 6 from being broken due to a fastening force applied thereto in mounting the stator 6.

[0075] The stepped areas 70b-1 each having steps at preset intervals as the stepped area 70b-1 extends in an outward radial direction of the cylindrical bearing supporting part 7a, and the flat areas 70b-2 between adjacent stepped areas 70b-1 and connected to the stepped areas 70b-1 in a circumferential direction with flat parts perpendicular thereto permit to increase bonding force to the tub 2 in the injection molding of the tub 2.

[0076] In addition to this, the circumferential rib 720b

at a position spaced a distance from an axis of the bearing supporting part 7a also increases a bonding force with the plastic in the injection molding of the tub 2.

[0077] Moreover, the through holes 730b in the stator fastening part 7b increases the bonding force with the plastic in the insert injecting molding of the bearing housing 7.

[0078] The fastening boss 70b with the stator fastening hole 700b in the bearing housing 7 can dispense with formation of fastening holes in the tub 2. additionally.

[0079] That is, in an embodiment of the present invention, the stator 6 is fastened to the stator fastening holes 700b in the fastening boss 70b of the stator fastening part 7b buried in the tub rear wall with bolts.

[0080] The positioning hole 710b formed adjacent to the stator fastening hole 700b of the stator fastening part 7b in correspondence to a positioning projection on the insulator of the stator 6 improves workability in mounting the stator 6 on the tub rear wall.

[0081] Of course, the positioning hole 710b in the stator fastening part 7b is formed, not covered with plastic, but exposed, and in a case the positioning hole is formed in the insulator, the positioning projection will be formed on the stator fastening part 7b.

[0082] Since the front end of the shaft 4 is fixed to the spider 10 in the rear wall of the drum 3, and a section of the shaft 4 from a part exposed to an outside of the spider 10 to the front bearing 600a has the brass bushing 11 forcibly press fit thereon, rusting of the shaft 4 is prevented.

[0083] The sealing member 12 on the outside surface of the bushing 11 prevents infiltration of water toward the bearing.

[0084] The circumferential bent part with a seating surface 130 for seating magnets M placed on an inside surface of a side wall 13b extended forward from an edge of a rear wall of the rotor 5 permits an easy fabrication of the rotor since the seating surface 130 supports the magnet M easily when the magnet M is attached to the inside surface of the rotor 5.

[0085] The hub 132 in a centre part of the rear wall 13a having through holes 131 permits to pass fastening members 15a, such as bolts, in mounting the rotor 5 on the shaft 4, and the plurality of radial cooling fins 133 each with a length permits blowing of air toward the stator 6 to cool heat from the stator 6 when the rotor 5 rotates.

[0086] The cooling fin 133 is formed by lancing to direct an opened side of the rotor 5, and a through hole 134 formed in the lancing serves as an air hole.

[0087] The rotor 5 formed of steel plate by pressing reduces a time period required for fabrication of the rotor 5, and improves productivity.

[0088] The embossing 135 between adjacent cooling fins 133 on the rear wall 13a of the rotor 5 improves an overall strength of the rotor 5, and the drain hole 136 in the embossing 135 permits to discharge water through the drain hole 136.

[0089] The connector 16, formed by a plastic injecting molding, has a vibration mode different from a vibration mode of the rotor 5 of steel plate, to attenuate vibration transmitted from the rotor 5 to the shaft 4.

[0090] The serration 164 in the inside circumferential surface of the hub of the connector 16 engaged with the serration 400 in the rear end part of the shaft 4 enables transmission of a rotation power from the rotor 5 to the shaft 4 through the connector 16 as it is.

[0091] FIG. 13 illustrates a perspective view of a stator in a driving part of a drum type washing machine of another embodiment of the present invention.

[0092] Referring to FIG. 13, the stator 6 of this embodiment includes a helical type core HC, an insulator 144 having the helical type core HC encapsulated therein, a coil wound on tooth portions 151 of the helical core HC, and fastening parts 143 formed as a unit with the insulator 144 so as to be projected toward an inside of the helical type core HC.

[0093] That is, the stator 6 in the embodiment does not have a structure in which the fastening parts are projected in a radial direction toward an inside of the helical type core HC from more than three positions, but a structure in which the fastening parts form a unit with the insulator 144 extended in a radial direction toward an inside of the helical type core HC.

[0094] Alike the foregoing embodiment, the helical type core HC has multiple layers formed by winding a steel plate in a helix starting from a bottom layer to a top layer, with a plurality of tooth portions 151 projected outwardly in a radial direction from a base part 150 of the helical type core HC, and recesses 152 in the base part 150 for reducing a stress in winding the helical type core HC.

[0095] There is a positioning hole 143g adjacent to the fastening hole 143a in the fastening part 143, if there is a positioning pin on the tub rear wall, for fitting in mounting the stator. Opposite to this, of course, the positioning pin may be formed adjacent to the fastening hole 143a, and the positioning hole may be formed in the tub rear wall.

[0096] Other parts and performances thereof of the embodiment are the same with the foregoing embodiment, of which repetitive descriptions are omitted.

[0097] The present invention is not limited to the described or illustrated embodiments, and is instead extends to the full scope of the appended claims.

[0098] For an example, the stator fastening part 7b may only have an outward radial direction extension from the cylindrical bearing supporting part 7a with stepped areas 70b-1 at preset intervals along a radial direction. Or, alternatively, the stator fastening part 7b may have alternate outward radial direction extensions from front part and rear part of the cylindrical bearing supporting part 7a in a circumferential direction connected at edges of the extensions substantially perpendicular to the extensions, without the stepped areas.

[0099] FIG. 14 illustrates a longitudinal section another

embodiment of a drum type washing machine.

[0100] Referring to FIG. 14, the drum type washing machine includes a tub 2 having a wall for holding washing water therein and mounting a driving part thereon, and a sleeve form of bearing supporting part 17 for supporting bearings, in which both the tub 2 and the bearing supporting part 17 are formed as one unit, a drum 3 rotatably arranged inside of the tub 2, a shaft 4 passed through the tub 2 and connected to the drum 3 for transmission of a driving power from a motor to the drum, at least one bearing 600a inside of the bearing supporting part 17 for supporting the shaft 4, a rotor 5 engaged to a rear end part of the shaft 4 to form the motor together with the stator 6, and the stator 6 mounted on the tub 2 on an inner side of the rotor 5 and an outer side of the bearing supporting part 17 with fastening members. The stator 6 includes an annular helical type core HC having multiple layers formed by winding a steel plate having tooth portions 151 and base part in a helix starting from a bottom layer to a top layer, an insulator having the helical type core HC encapsulated therein, a coil wound on the tooth portions 151, and fastening parts formed as a unit with the insulator 144, having fastening holes projected toward an inside of the helical type core HC for fastening to the bearing supporting part 17.

[0101] A plurality of fastening holes are provided in an outer region of the bearing supporting part 17 of the tub 2 for mounting the stator 6 of motor with fastening members. There is a metal tube 143p or a spring pin forcibly inserted in the fastening hole 143a of the fastening part 143.

[0102] Both the tub 2 and the bearing supporting part 17 may be formed by plastic injection molding, or the tub 2 may be formed of plastic, and the bearing supporting part 17 may be formed of a metal, such as an aluminium alloy.

[0103] More preferably, in the plastic injection molding process of the tub 2, the tub 2 is injection molded with a tub supporting plate 18 of a metal formed as a separate piece from the bearing supporting part buried in an outer region of the bearing supporting part 17.

[0104] Other parts not described herein are the same with the foregoing embodiment, and repetitive description of which will be omitted.

[0105] The performance of the embodiment will be described.

[0106] When a current flows to the stator 6, to rotate the rotor 5, the shaft 4 connected to the rotor 5 rotates. The shaft 4 rotates supported on a front bearing 600a and a rear bearing 600b inside of the bearing supporting part 17.

[0107] Load on the shaft 4 is transmitted to the front and rear bearings 600a, and 600b, and, therefrom, to the bearing supporting part 17. Since the bearing supporting part 17 is formed as a unit with the tub rear part, the bearing supporting part 17 can support the shaft 4 stably.

[0108] The tub supporting plate 18 of a metal formed

as a separate piece from the bearing supporting part, and buried in an outer region of the bearing supporting part 17 in the injection molding of the tub 2 permits to dispense with a separate reinforcing liner attached to the tub rear wall, enough to secure a supporting force for the stator 6 mounted on the tub rear wall even if the brushless d.c. motor is mounted on the tub wall directly.

[0109] It will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the scope of the invention. Thus, it is intended that the present invention cover the modifications and variations of this invention provided they come within the scope of the appended claims.

[0110] Embodiments of the drum type washing machine of the present invention have the following advantages.

[0111] First, the direct drive type motor reduces noise, out of order, and power loss, and the bearing housing of a metal can be applied to a product with a drying function, as the bearing housing has no thermal deformation. Such a product may be a combined washer-dryer, or a dryer.

[0112] Second, a rotor 5 formed by pressing a steel plate reduces a fabrication time period, and improves productivity.

[0113] Third, the helical type core permits to reduce waste of material, easy fabrication, and increase a rigidity of the fastening part of the stator 6 to reduce noise and vibration, and improve mechanical reliability, and a lifetime.

[0114] Fourth, the difference between the vibration modes of the rotor and the connector permits to reduce vibration transmitted from the rotor to the shaft, and the stator fastening part 7b permits rigid mounting of the stator 6 on the tub rear wall, and maintenance of concentricity of the stator 6, without damage of the tub rear wall.

[0115] Fifth, the elimination of tub supporter fitting work from the assembly line permits to simplify an assembly process, and easy maintenance by a serviceman in repair and replacement of component.

[0116] Sixth, even where a brushless d.c. motor has a net stator weight over 1.5kg, and a rotation speed varied in a range of 0 - 2000 RPM, or over and the motor is mounted on the tub wall directly, the tub rear wall can securely support the stator.

Claims

1. A drum type washing machine comprising:

a tub of plastic having a wall for holding washing water therein and mounting a driving part thereon;
a drum rotatably arranged inside of the tub;
a shaft passed through the tub and connected to the drum for transmission of a driving power

from a motor to the drum;

at least one bearing for supporting the shaft;
a bearing housing having a bearing supporting part formed as a sleeve, and a stator fastening part extended in a radial direction from the bearing supporting part, wherein both of the bearing supporting part and the stator fastening part are inserted in a tub rear wall, while stator fastening holes in the stator fastening part are exposed;

a rotor engaged to a rear end part of the shaft to form the motor together with the stator; and
the stator mounted on the stator fastening part of the bearing housing with fastening members on an inner side of the rotor to form the motor together with the rotor.

2. A drum type washing machine comprising:

a tub of a plastic having a wall for holding washing water therein and mounting a driving part thereon;

a drum rotatably arranged inside of the tub;

a shaft passed through the tub and connected to the drum for transmission of a driving power from a motor to the drum;

at least one bearing for supporting the shaft;
a bearing housing having a bearing supporting part, formed as a sleeve and inserted in the tub rear wall, and a stator fastening part formed as a unit with the bearing supporting part extended from the bearing supporting part exposed to an outside of the tub, with stator fastening holes formed in an exposed part of the stator fastening part;

a rotor engaged to a rear end part of the shaft to form the motor together with the stator; and
the stator mounted on the stator fastening part of the bearing housing with fastening members on an inner side of the rotor to form the motor together with the rotor.

3. A drum type washing machine as claimed in claim 1 or 2,

wherein the stator includes;

an annular helical type core having multiple layers formed by winding a steel plate having tooth portions and a base part in a helix starting from a bottom layer to a top layer,

an insulator having the helical type core encapsulated therein,

a coil wound on the tooth portions, and

fastening parts formed as a unit with the insulator, having fastening holes projected toward an inside of the helical type core for fastening the stator to the bearing housing.

4. A drum type washing machine as claimed in claim

- 2 wherein the stator has a weight heavier than 1.5 kg.
5. A drum type washing machine according to any preceding claim wherein
 - the fastening parts formed as a unit with the insulator have three or more than three fastening holes projected toward an inside of the helical type core for fastening the stator to the bearing housing.
 6. The drum type washing machine as claimed in any preceding claim, wherein the fastening part has a height greater than 20% of a total stack height of the helical type core.
 7. The drum type washing machine as claimed in any preceding claim, wherein the fastening hole in the fastening part has a spring pin.
 8. The drum type washing machine as claimed in any preceding claim, wherein the fastening hole in the fastening part has a metal tube press fit therein.
 9. The drum type washing machine as claimed in claim 1 or 2, wherein the stator includes;
 - a core,
 - an insulator having the core encapsulated therein,
 - a coil wound on tooth portions, and
 - fastening parts formed as a unit with the insulator, having fastening holes projected toward an inside of the core for fastening the stator to the bearing housing.
 10. The drum type washing machine as claimed in claim 1 or 2, wherein the stator includes;
 - a core having a helical wound stack,
 - an insulator of an insulating material having the core encapsulated therein,
 - a coil wound on tooth portions of the helical core, and
 - three or more than three fastening parts formed as a unit with the insulator, projected toward an inside of the core.
 11. The drum type washing machine as claimed in claim 1, wherein the stator fastening part of the bearing housing includes an extension in an outward radial direction from the cylindrical bearing supporting part, having steps along the radial direction at preset intervals.
 12. The drum type washing machine as claimed in claim 1, wherein the stator fastening part includes alternate outward radial direction extensions from front part, and rear part of the cylindrical bearing supporting part in a circumferential direction connected at edges of the extensions substantially perpendicular to the extensions, or,
 - wherein the stator fastening part includes alternate outward radial direction extensions from front part, and rear part of the cylindrical bearing supporting part in a circumferential direction connected at edges of the extensions substantially perpendicular to the extensions, the extension having steps at preset intervals along the radial direction.
 13. The drum type washing machine as claimed in claim 1 or 2, further comprising a positioning hole adjacent to the stator fastening hole in the stator fastening part in correspondence to the positioning pin on the stator.
 14. The drum type washing machine as claimed in claim 1, wherein the tub rear wall includes bosses at parts of the tub rear wall opposite to the stator fastening holes for preventing the stator fastening part from coming into direct contact with the stator, thereby preventing the insulator of the stator from being broken due to a fastening force applied thereto in mounting the stator.
 15. The drum type washing machine as claimed in claim 1 or 2, wherein the stator fastening part includes a rib formed thereon for increasing a bonding force with a plastic in the injection molding of the tub.
 16. The drum type washing machine as claimed in claim 15, wherein the rib is formed along a circumferential direction and/or:
 - wherein the rib has fastening bosses each with the stator fastening hole formed therein.
 17. The drum type washing machine as claimed in claim 1 or 2, wherein the stator fastening part includes a plurality of radial direction outward extensions from the cylindrical bearing supporting part separated at regular intervals in a circumferential direction to form a plurality of separated radial segments.
 18. The drum type washing machine as claimed in claim 10, wherein the helical type core includes;
 - multiple layers formed by winding in a helix starting from a bottom layer to a top layer,
 - tooth portions projected outwardly in a radial direction from a base part, and
 - recesses in the base part for reducing stress in the winding of the helical type core.
 19. The drum type washing machine as claimed in claim 18, wherein the helical type core includes;
 - rivets passed through through holes in the base part for fastening the layers, respectively.
 20. The drum type washing machine as claimed in claim 10, wherein the helical type core includes;

welded parts of the layer with the base part at the bottom layer and the top layer where the winding starts and ends respectively.

21. The drum type washing machine as claimed in claim 18, wherein the recess is rectangular, or trapezoidal. 5
22. A drum type washing machine comprising: 10
- a tub having a wall for holding washing water therein and mounting a driving part thereon, and a bearing supporting part formed as a sleeve for supporting bearings, in which both the tub and the bearing supporting part are formed as one unit; 15
 - a drum rotatably arranged inside of the tub;
 - a shaft passed through the tub and connected to the drum for transmission of a driving power from a motor to the drum; 20
 - at least one bearing inside of the bearing supporting part for supporting the shaft;
 - a rotor engaged to a rear end part of the shaft to form the motor together with the stator; and 25
 - the stator mounted on the tub on an inner side of the rotor and an outer side of the bearing supporting part with fastening members,
- wherein the stator includes;
- an annular helical type core having multiple layers formed by winding a steel plate having tooth portions and base part in a helix starting from a bottom layer to a top layer, 30
 - an insulator having the helical type core encapsulated therein, 35
 - a coil wound on the tooth portions, and
 - fastening parts formed as a unit with the insulator, having fastening holes projected toward an inside of the helical type core for fastening the stator to the bearing housing. 40
23. The drum type washing machine as claimed in claim 22, wherein the tub includes a metal tub supporting plate built-in an outer region of the bearing supporting part formed as a separate piece from the bearing supporting part. 45
24. The drum type washing machine as claimed in claim 23, wherein the tub is injection molded in a state the tub supporting plate is buried in the tub. 50

FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12A




FIG. 12B




FIG. 13





FIG. 14





European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 03 25 7739

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	EP 1 094 144 A (LG ELECTRONICS INC) 25 April 2001 (2001-04-25)	1,2,9,11	D06F37/30
Y	* column 4, line 15 - column 14, line 45; figures 2B,2C,7 *	3,5,22	
A		4,6-8, 10, 12-21, 23,24	
X	US 5 862 686 A (SKRIPPEK JOERG) 26 January 1999 (1999-01-26)	1,2,11	
Y	* column 4, line 14 - column 4, line 67; figure 2 *	3,5,22	
A		4,6-10, 12-21, 23,24	
Y	EP 0 620 308 A (FISHER & PAYKEL) 19 October 1994 (1994-10-19)	3,5,9, 10,18-24	TECHNICAL FIELDS SEARCHED (Int.Cl.7) D06F
A	* column 3, line 4 - column 20, line 41; figures 3,2,5 *	1,2,4, 6-8, 11-17	
Y	EP 0 629 735 A (FISHER & PAYKEL) 21 December 1994 (1994-12-21)	3,5,9, 10,18-24	
A	* column 4, line 35 - column 4, line 53; figure 9 *	1,2,4, 6-8, 11-17	
X	EP 1 116 812 A (TOKYO SHIBAURA ELECTRIC CO) 18 July 2001 (2001-07-18)	1,2	
A	* figure 1 *	3-24	
X	EP 1 079 014 A (TOKYO SHIBAURA ELECTRIC CO) 28 February 2001 (2001-02-28)	1,2	
A	* figures 2,3 *	3-24	
-/--			
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 8 March 2004	Examiner Spitzer, B
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03 82 (P04C01)



European Patent
Office

EUROPEAN SEARCH REPORT

Application Number
EP 03 25 7739

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.7)
X	EP 1 094 145 A (LG ELECTRONICS INC) 25 April 2001 (2001-04-25)	1	
A	* the whole document *	2-24	

A	EP 0 780 506 A (BOSCH SIEMENS HAUSGERAETE) 25 June 1997 (1997-06-25)	1-24	
	* the whole document *		

			TECHNICAL FIELDS SEARCHED (Int.Cl.7)
The present search report has been drawn up for all claims			
Place of search MUNICH		Date of completion of the search 8 March 2004	Examiner Spitzer, B
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons & : member of the same patent family, corresponding document</p>			

EPO FORM 1503 03/02 (P04C01)

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 03 25 7739

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

08-03-2004

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1094144	A	25-04-2001	KR 2001037666 A	15-05-2001
			KR 2001037667 A	15-05-2001
			KR 2001037668 A	15-05-2001
			KR 2001037670 A	15-05-2001
			AU 753411 B2	17-10-2002
			AU 6656900 A	03-05-2001
			CN 1293277 A ,B	02-05-2001
			DE 60007259 D1	29-01-2004
			EP 1094144 A2	25-04-2001
			JP 3432206 B2	04-08-2003
			JP 2001178989 A	03-07-2001
			US 6510716 B1	28-01-2003
US 5862686	A	26-01-1999	DE 19547745 A1	26-06-1997
			AT 229584 T	15-12-2002
			AU 720902 B2	15-06-2000
			AU 7540496 A	26-06-1997
			BR 9606097 A	03-11-1998
			DE 59609971 D1	23-01-2003
			EP 0780507 A2	25-06-1997
			ES 2188712 T3	01-07-2003
			JP 9182369 A	11-07-1997
			TR 970540 A2	21-07-1997
			US 5894746 A	20-04-1999
EP 0620308	A	19-10-1994	NZ 226374 A	26-10-1994
			EP 0620308 A2	19-10-1994
			AT 114177 T	15-12-1994
			AT 169698 T	15-08-1998
			AU 623173 B2	07-05-1992
			AU 4147789 A	03-05-1990
			AU 642032 B2	07-10-1993
			AU 8158591 A	31-10-1991
			CA 1332434 C	11-10-1994
			CA 1335939 C	20-06-1995
			DE 68919400 D1	22-12-1994
			DE 68919400 T2	18-05-1995
			DE 68928786 D1	17-09-1998
			DE 68928786 T2	24-12-1998
			EP 0361775 A2	04-04-1990
			ES 2066859 T3	16-03-1995
			ES 2121108 T3	16-11-1998
			HK 103895 A	07-07-1995
			HK 1011390 A1	21-09-2001
			JP 2777109 B2	16-07-1998
			JP 9103596 A	22-04-1997

EPO FORM P0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 03 25 7739

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report.
The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

08-03-2004

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 0620308	A		JP 2211046 A	22-08-1990
			JP 2806570 B2	30-09-1998
			MX 170371 B	18-08-1993
			NZ 247033 A	26-10-1994
			SG 55083 A1	21-12-1998
			US 5040285 A	20-08-1991
			US 5150589 A	29-09-1992
EP 0629735	A	21-12-1994	NZ 215389 A	25-02-1992
			EP 0629735 A2	21-12-1994
			AT 116387 T	15-01-1995
			AU 614696 B2	05-09-1991
			AU 6088390 A	15-11-1990
			AU 619414 B2	23-01-1992
			AU 6088490 A	29-11-1990
			AU 599960 B2	02-08-1990
			AU 6968587 A	10-09-1987
			BR 8701058 A	22-12-1987
			CA 1331103 C	02-08-1994
			CA 1331104 C	02-08-1994
			CA 1329235 C	03-05-1994
			DE 3750910 D1	09-02-1995
			DE 3750910 T2	11-05-1995
			EP 0239261 A2	30-09-1987
			HK 86695 A	09-06-1995
			JP 7079905 B	30-08-1995
			JP 62268343 A	20-11-1987
			NZ 234546 A	25-02-1992
			NZ 234547 A	25-02-1992
			SG 49760 A1	15-06-1998
			US 4741183 A	03-05-1988
			US 5353613 A	11-10-1994
			US 4853571 A	01-08-1989
			US 4813248 A	21-03-1989
			US 5266855 A	30-11-1993
			ZA 8701604 A	25-08-1987
EP 1116812	A	18-07-2001	JP 2000279679 A	10-10-2000
			JP 2000342880 A	12-12-2000
			EP 1116812 A1	18-07-2001
			US 6539753 B1	01-04-2003
			CN 1297498 T	30-05-2001
			WO 0060157 A1	12-10-2000
			TW 470801 B	01-01-2002
EP 1079014	A	28-02-2001	JP 2000262796 A	26-09-2000

EPO FORM P4459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

**ANNEX TO THE EUROPEAN SEARCH REPORT
ON EUROPEAN PATENT APPLICATION NO.**

EP 03 25 7739

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

08-03-2004

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
EP 1079014	A		EP 1079014 A1	28-02-2001
			US 6557383 B1	06-05-2003
			CN 1134562 B	14-01-2004
			WO 0055413 A1	21-09-2000
			TW 510932 B	21-11-2002

EP 1094145	A	25-04-2001	KR 2001037517 A	15-05-2001
			KR 2001037518 A	15-05-2001
			AU 4875800 A	26-04-2001
			CN 1293276 A	02-05-2001
			EP 1094145 A2	25-04-2001
			JP 2001113089 A	24-04-2001
			JP 2004000608 A	08-01-2004
			US 2003006665 A1	09-01-2003
			US 6460382 B1	08-10-2002

EP 0780506	A	25-06-1997	DE 19547456 A1	26-06-1997
			AT 202164 T	15-06-2001
			AU 725857 B2	26-10-2000
			AU 7543896 A	26-06-1997
			BR 9606043 A	25-08-1998
			CN 1161391 A ,B	08-10-1997
			DE 59607080 D1	19-07-2001
			EP 0780506 A1	25-06-1997
			ES 2157387 T3	16-08-2001
			GR 3036255 T3	31-10-2001
			JP 9182370 A	11-07-1997
			NZ 299861 A	27-05-1998
			NZ 299862 A	27-05-1998
			SI 780506 T1	31-08-2001
			TR 970542 A2	21-07-1997

EPO FORM P/0459

For more details about this annex : see Official Journal of the European Patent Office, No. 12/82

PUB-NO: EP001428924A1
DOCUMENT-IDENTIFIER: EP 1428924 A1
TITLE: Drum type washing machine
PUBN-DATE: June 16, 2004

INVENTOR-INFORMATION:

NAME	COUNTRY
KIM, GON	KR
HUR, CHI WAN	KR
KANG, YU BEOM	KR
JE, SANG MAN	KR
CHOI, KANG MO	KR
KIM, JAE KYUM	KR
KWON, HO CHEOL	KR

ASSIGNEE-INFORMATION:

NAME	COUNTRY
LG ELECTRONICS INC	KR

APPL-NO: EP03257739
APPL-DATE: December 9, 2003

PRIORITY-DATA: KR20020078337A (December 10,
2002) , KR20030086841A (December
2, 2003)

INT-CL (IPC): D06F037/30

EUR-CL (EPC): D06F037/30 , H02K001/14 ,
H02K001/18 , H02K007/08

ABSTRACT:

CHG DATE=20040626 STATUS=O>Drum type washing machine including a tub of plastic having a wall for holding washing water therein and mounting a driving part thereon, a drum rotatably arranged inside of the tub, a shaft passed through the tub and connected to the drum for transmission of a driving power from a motor to the drum, at least one bearing for supporting the shaft, a bearing housing having a bearing supporting part formed as a sleeve, and a stator fastening part extended in a radial direction from the bearing supporting part, wherein both of the bearing supporting part and the stator fastening part are inserted in a tub rear wall, while stator fastening holes in the stator fastening part are exposed, a rotor engaged to a rear end part of the shaft to form the motor together with the stator, and the stator mounted on the stator fastening part of the bearing housing with fastening members on an inner side of the rotor to form the motor together with the rotor, wherein the stator includes an annular helical type core having multiple layers formed by winding a steel plate having tooth portions and a base part in a helix starting from a bottom layer to a top layer, an insulator having the helical type core encapsulated therein, a coil wound on the tooth portions, and fastening parts formed as a unit with the insulator, having fastening holes projected toward an inside of the helical type core for fastening the stator to the bearing housing, thereby reducing a weight of required material, simplifying an assembly process, and

assure stable mounting of the stator on the tub.



PTO/SB/08a/b (05-03)

Approved for use through 05/31/2003. OMB 0651-0031

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Substitute for form 1449/PTO

**INFORMATION DISCLOSURE
STATEMENT BY APPLICANT**

(use as many sheets as necessary)

Sheet	1	of	1
-------	---	----	---

Complete if Known

Application Number	11/312,527
Filing Date	December 21, 2005
First Named Inventor	KIM, Gon
Art Unit	1746
Examiner Name	Rita Ramesh PATEL
Attorney Docket Number	9988.095.20

U.S. PATENT DOCUMENTS

Examiner Initials*	Cite No. ¹	Document Number Number-Kind Code ² (if known)	Publication Date MM-DD-YYYY	Name of Patentee or Applicant of Cited Document	Pages, Columns, Lines, Where Relevant Passages or Relevant Figures Appear
	AA				

FOREIGN PATENT DOCUMENTS

Examiner Initials*	Cite No. ¹	Foreign Patent Document Country Code ³ -Number ⁴ -Kind Code ⁵ (if known)	Publication Date MM-DD-YYYY	Name of Patentee or Applicant of Cited Document	Pages, Columns, Lines, Where Relevant Passages or Relevant Figures Appear	T ⁶
/RRP/	BA	WO 01/44556 A1	06/21/2001	Heyder et al.		

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant. ¹ Applicant's unique citation designation number (optional). ² See Kinds Codes of USPTO Patent Documents at www.uspto.gov or MPEP 901.04. ³ Enter Office that issued the document, by the two-letter code (WIPO Standard ST.3). ⁴ For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the application number of the patent document. ⁵ Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST. 16 if possible. ⁶ Applicant is to place a check mark here if English language Translation is attached.

NON PATENT LITERATURE DOCUMENTS

Examiner Initials*	Cite No. ¹	Include name of the author (in CAPITAL LETTERS), title of the article (when appropriate), title of the item (book, magazine, journal, serial, symposium, catalog, etc.), date, page(s), volume-issue number(s), publisher, city and/or country where published.	T ²
	CA		

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant. ¹ Applicant's unique citation designation number (optional). ² Applicant is to place a check mark here if English language Translation is attached.

DC:50530178.1

Examiner Signature	/Rita R. Patel/	Date Considered	03/25/2008
-----------------------	-----------------	--------------------	------------

Substitute for form 1449/PTO

**INFORMATION DISCLOSURE
STATEMENT BY APPLICANT**

(use as many sheets as necessary)

Sheet	1	of	1	Complete if Known	
-------	---	----	---	-------------------	--

Application Number	11/312/527
Filing Date	December 21, 2005
First Named Inventor	KIM, Gon
Art Unit	1746
Examiner Name	Rita Ramesh PATEL
Attorney Docket Number	9988.095.20

U.S. PATENT DOCUMENTS

Examiner Initials*	Cite No. ¹	Document Number Number-Kind Code ² (if known)	Publication Date MM-DD-YYYY	Name of Patentee or Applicant of Cited Document	Pages, Columns, Lines, Where Relevant Passages or Relevant Figures Appear
/RRP/	AA	2,705,763	04/05/1955	A Skrobishch	
/RRP/	AB	5,266,855	11/1993	Smith et al.	
/RRP/	AC	5,040,285	08/20/1991	Williams et al.	
/RRP/	AD	6,460,382	10/2002	Kim et al.	
/RRP/	AE	5,809,809	09/22/1998	Neumann	
/RRP/	AF	3,886,256	05/27/1975	Ohuchi et al.	
/RRP/	AG	6,257,027 B1	07/10/2001	Imai	
/RRP/	AH	6,477,869 B2	11/12/2002	Heyder et al.	

FOREIGN PATENT DOCUMENTS

Examiner Initials*	Cite No. ¹	Foreign Patent Document Country Code ³ -Number ⁴ -Kind Code ⁵ (if known)	Publication Date MM-DD-YYYY	Name of Patentee or Applicant of Cited Document	Pages, Columns, Lines, Where Relevant Passages or Relevant Figures Appear	T ⁶
/RRP/	BA	KR 1020010088215-A	09/26/2001	LG Electronics Inc.		
/RRP/	BB	CN 1274782	11/29/2000	Tokyo Shibaura Electric Co.		
/RRP/	BC	CN 1293276	05/02/2001	LG Electronics Inc.		
/RRP/	BD	AU 199675438-B2	12/18/1996	Bosch-Siemens Hausgerate Gmbh		
/RRP/	BE	AU 199675404-B2	12/17/1996	Bosch-Siemens Hausgerate Gmbh		
/RRP/	BF	JP 2000-116037	04/21/2000			
/RRP/	BG	WO 01/44556-A1	06/21/2001			
/RRP/	BH	EP 1094145-A2	04/25/200			
/RRP/	BI	EP 0381775-A2	04/04/1990			
/RRP/	BJ	EP 1094144-A2	04/25/2001			
/RRP/	BK	EP 0620308-A2	10/19/1994			
/RRP/	BL	DE 19859568	06/29/2000	BSH Bosch Siemens Hausgerate		
/RRP/	BM	GB 2332212-A	06/16/1999	Toshiba		
/RRP/	BN	EP 1079014-A1	02/28/2001	Toshiba		
/RRP/	BO	WO 02/084842-A1	10/24/2002	Matsushita Seiko		
/RRP/	BP	JP 58207834	12/03/1983	Matsushita Electric		
/RRP/	BQ	GB 2030896-A	04/16/1980	Nippondenso		
/RRP/	BR	EP 0219115-A2	04/22/1987	Zanussi Elettrodomestici		
/RRP/	BS	GB 2333300-A	07/21/1999	Electrolux Zanussi		
/RRP/	BT	DE 4335966	04/27/1995	Licentia GMBH		
/RRP/	BU	EP 1116812-A1	07/18/2001	Toshiba		

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant. ¹ Applicant's unique citation designation number (optional). ² See Kinds Codes of USPTO Patent Documents at www.uspto.gov or MPEP 901.04. ³ Enter Office that issued the document, by the two-letter code (WIPO Standard ST.3). ⁴ For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the application number of the patent document. ⁵ Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST. 16 if possible. ⁶ Applicant is to place a check mark here if English language Translation is attached.

NON PATENT LITERATURE DOCUMENTS

Examiner Initials*	Cite No. ¹	Include name of the author (in CAPITAL LETTERS), title of the article (when appropriate), title of the item (book, magazine, journal, serial, symposium, catalog, etc.), date, page(s), volume-issue number(s), publisher, city and/or country where published.	T ²
	CA		

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant. ¹ Applicant's unique citation designation number (optional). ² Applicant is to place a check mark here if English language Translation is attached.

DC:50507843.1

Examiner Signature	/Rita R. Patel/	Date Considered	03/25/2008
--------------------	-----------------	-----------------	------------



PTO/SB/08a/b (05-03)
Approved for use through 05/31/2003. OMB 0651-0031
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Patent Mark Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Substitute for form 1449/PTO		Complete if Known			
INFORMATION DISCLOSURE STATEMENT BY APPLICANT (use as many sheets as necessary)		Application Number	11/312/527		
		Filing Date	December 21, 2005		
		First Named Inventor	KIM, Gon		
		Art Unit	1746		
		Examiner Name	Rita Ramesh PATEL		
Sheet	1	of	1	Attorney Docket Number	9988.095.20

U.S. PATENT DOCUMENTS						
Examiner Initials*	Cite No. ¹	Document Number Number-Kind Code ² (if known)	Publication Date MM-DD-YYYY	Name of Patentee or Applicant of Cited Document	Pages, Columns, Lines, Where Relevant Passages or Relevant Figures Appear	
/RRP/	AA	5,489,811	02/06/1996	Kern et al.		
FOREIGN PATENT DOCUMENTS						
Examiner Initials*	Cite No. ¹	Foreign Patent Document Country Code ³ -Number ⁴ -Kind Code ⁵ (if known)	Publication Date MM-DD-YYYY	Name of Patentee or Applicant of Cited Document	Pages, Columns, Lines, Where Relevant Passages or Relevant Figures Appear	T ⁶
/RRP/	BA	KR 1999-0081170	11/15/1999	LG Electronics Inc.		
/RRP/	BB	KR 1999-0030909	05/06/1999	LG Electronics Inc.		
/RRP/	BC	KR 20-1992-0012151	07/25/1992	Gold Start		
/RRP/	BD	KR 20-1998-0058943	10/26/1998	Samsung Electronics, Inc.		

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant. ¹ Applicant's unique citation designation number (optional). ² See Kinds Codes of USPTO Patent Documents at www.uspto.gov or MPEP 901.04. ³ Enter Office that issued the document, by the two-letter code (WIPO Standard ST.3). ⁴ For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the application number of the patent document. ⁵ Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST. 16 if possible. ⁶ Applicant is to place a check mark here if English language Translation is attached.

NON PATENT LITERATURE DOCUMENTS			
Examiner Initials*	Cite No. ¹	Include name of the author (in CAPITAL LETTERS), title of the article (when appropriate), title of the item (book, magazine, journal, serial, symposium, catalog, etc.), date, page(s), volume-issue number(s), publisher, city and/or country where published.	T ²
	CA		

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through citation if not in conformance and not considered. Include copy of this form with next communication to applicant. ¹ Applicant's unique citation designation number (optional). ² Applicant is to place a check mark here if English language Translation is attached.

DC:50536991.1

Examiner Signature	/Rita R. Patel/	Date Considered	03/26/2008
--------------------	-----------------	-----------------	------------